



1. Product and Company Identification

Material name	Manganese Bronze Alloys
Revision date	06-30-2011
Version #	03
CAS #	Mixture
Product code	C86100, C86200, C86300, C86400, C86500, C86700, C99700, ATI, 861
MSDS Number	7
Product use	Manufacturing
Manufacturer/Supplier	Concast Metal Products Company 131 Myoma Road (PO Box 816) Mars, PA 16046 dpl@concast.com or adk@concast.com Telephone 1-800-626-7071 Contact Person: Dominic LeMaire or Andy Krowsoski
Emergency	1-800-424-9300 Chemtrec (24-hrs)
2. Hazards Identification	
Physical state	Solid.
Appearance	Shapes, Solids, Tubes & Turnings.
Emergency overview	WARNING
	Possible reproductive hazard - contains material that may cause adverse reproductive effects. Possible cancer hazard - may cause cancer based on animal data. Harmful if inhaled or swallowed. May cause allergic skin reaction. Dusts may irritate the respiratory tract, skin and eyes.
	Warning: May Form Combustible (Explosive) Dust - Air Mixtures
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects	
Routes of exposure	Inhalation. Skin contact. Eye contact. Ingestion.
Eyes	Molten material will produce thermal burns. Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eyes.
Skin	Dust may irritate skin. May cause allergic skin reaction. Hot or molten material may produce thermal burns. Workers allergic to nickel may develop eczema or rashes.
Inhalation	Harmful if inhaled. Elevated temperatures or mechanical action may form dust and fumes which may be irritating to mucous membranes and respiratory tract.
Ingestion	Not relevant, due to the form of the product in its manufactured and shipped state. However, harmful if swallowed.
Target organs	Lungs. Reproductive system. Respiratory system.
Chronic effects	Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Lead is accumulated in the body and may cause damage to the brain and nervous system after prolonged exposure. Exposure to manganese fume/dust can affect the central nervous system (apathy, drowsiness, weakness and other chronic symptoms such as postural tremors). Contains nickel, which can cause lung or nasal cancer. Long-term breathing of this material may cause chronic lung disease. Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis (stannosis). The effects might be delayed.
Signs and symptoms	Irritation of nose and throat. Irritation of eyes and mucous membranes. Coughing. Shortness of breath. Wheezing. Sensitization. The principal symptoms of lead poisoning are gastro-intestinal or central nervous system disturbances and anemia.
Potential environmental effects	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Copper	7440-50-8	54-66
Manganese	7439-96-5	0.1-15
Aluminum	7429-90-5	0.5-7.5
Nickel	7440-02-0	0-6
Lead	7439-92-1	0-2.0
Tin	7440-31-5	0-1.5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The alloy contains additional alloying elements at concentrations below disclosure requirements. At temperatures above the melting point the alloys may liberate fumes containing oxides of alloying elements.

4. First Aid Measures

First aid procedures	
Eye contact	Do not rub eyes. Remove any contact lenses. Flush eyes thoroughly with water, taking care to rinse under eyelids. If irritation persists, continue flushing for 15 minutes, rinsing from time to time under eyelids. If discomfort continues, consult a physician.
Skin contact	Contact with dust: Wash skin with soap and water. In case of allergic reaction or other skin disorders: Seek medical attention and bring along these instructions. In case of contact with hot or molten product, cool rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Cuts or abrasions should be treated promptly with thorough cleansing of the affected area.
Inhalation	In case of exposure to fumes or particulates: Get medical attention if discomfort persists.
Ingestion	Rinse mouth thoroughly if dust is ingested. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort continues.
Notes to physician	Treat symptomatically. Symptoms may be delayed.
General advice	Get medical attention if any discomfort develops. Seek medical attention for all burns, regardless how minor they may seem. Show this safety data sheet to the doctor in attendance.

5. Fire Fighting Measures

Flammable properties Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air. In a fire, nickel may form nickel carbonyl, a highly toxic substance and known carcinogen.

Extinguishing media	
Suitable extinguishing media	Special powder against metal fires. Dry sand.
Unsuitable extinguishing media	Do not use water or halogenated extinguishing media. Do not use water on molten metal: Explosion hazard could result.
Protection of firefighters	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk.
Hazardous combustion products	Metal oxides. Aluminium oxides.

6. Accidental Release Measures

Personal precautions	Ensure adequate ventilation. Avoid inhalation of dust and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.
Environmental precautions	Avoid release to the environment. Do not contaminate water.
Methods for containment	Not applicable.

Methods for cleaning up	Avoid dust formation. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal. Collect dust using a vacuum cleaner equipped with HEPA filter. If not possible, gently moisten dust before it is collected with shovel, broom or the like. The vacuum cleaner should be explosion-proofed. This material and its container must be disposed of as hazardous waste.
Other information	Clean up in accordance with all applicable regulations.
7. Handling and Storage	
Handling	Follow special national provisions related to work with lead and its compounds. Pregnant women should not work with the product, if there is the least risk of lead exposure. Welding, burning, sawing, brazing, grinding or machining operations may generate fumes and dusts of metal oxides. Provide adequate ventilation. Avoid contact with sharp edges and hot surfaces. Avoid inhalation of dust and contact with skin and eyes. Avoid generation and spreading of dust and fumes. Avoid contact with hot or molten material. Dust clouds may be explosive under certain conditions. Take precautionary measures against static discharges when there is a risk of dust explosion. Use explosion-proof electrical equipment if airborne dust levels are high. To prevent and minimize fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system. Wear appropriate personal protective equipment. Do not use water on molten metal. Do not eat, drink or smoke when using the product. Keep the workplace clean. Observe good industrial hygiene practices.
Storage	Keep dry. Store away from incompatible materials.

8. Exposure Controls / Personal Protection

Occupational exposure limits

Manganese (7439-96-5)

Nickel (7440-02-0)

Tin (7440-31-5)

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Aluminum (7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Copper (7440-50-8)	TWA	0.2 mg/m3	Fume.
		1 mg/m3	Dust and mist.
Lead (7439-92-1)	TWA	0.05 mg/m3	
Manganese (7439-96-5)	TWA	0.2 mg/m3	
Nickel (7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Tin (7440-31-5)	TWA	2 mg/m3	
US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	Form
Aluminum (7429-90-5)	PEL	15 mg/m3	Total dust.
		5 mg/m3	Respirable dust.
Copper (7440-50-8)	PEL	0.1 mg/m3	Fume.
		1 mg/m3	Dust and mist.
Lead (7439-92-1)	TWA	0.05 mg/m3	
Manganese (7439-96-5)	Ceiling	5 mg/m3	Fume.
Nickel (7440-02-0)	PEL	1 mg/m3	
Tin (7440-31-5)	PEL	2 mg/m3	
Canada. Alberta OELs (Occupati	ional Health & Safety Code, Sch	nedule 1, Table 2)	
Components	Туре	Value	Form
	TWA	5 mg/m3	Pyrophoric powder.
````		10 mg/m3	Dust.
Copper (7440-50-8)	TWA	0.2 mg/m3	Fume.
•• • •		1 mg/m3	Dust and mist.
Lead (7439-92-1)	TWA	0.05 mg/m3	
· · · · · · · · · · · · · · · · · · ·			

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

TWA

TWA

TWA

Components	Туре	Value	Form
Aluminum (7429-90-5)	TWA	1 mg/m3	Respirable.
Copper (7440-50-8)	TWA	0.2 mg/m3	Fume.
		1 mg/m3	Dust and mist.
Lead (7439-92-1)	TWA	0.05 mg/m3	

0.2 mg/m3

1.5 mg/m3

2 mg/m3

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Safety Regulation 296/97, a	s amended)		
Components	Туре	Value	Form
Manganese (7439-96-5)	TWA	0.2 mg/m3	
Nickel (7440-02-0)	TWA	0.05 mg/m3	
Tin (7440-31-5)	TWA	2 mg/m3	
Canada. Ontario OELs. (Min	nistry of Labor - Control of Exposure t	to Biological or Chemical Ag	ents)
Components	Туре	Value	Form
Aluminum (7429-90-5)	TWA	5 mg/m3	Welding fume.
		10 mg/m3	Dust.
Copper (7440-50-8)	TWA	0.2 mg/m3	Fume.
		1 mg/m3	Dust and mist.
Lead (7439-92-1)	TWA	0.05 mg/m3	
Manganese (7439-96-5)	TWA	0.2 mg/m3	
Nickel (7440-02-0)	TWA	1 mg/m3	Inhalable
Tin (7440-31-5)	TWA	2 mg/m3	innalable
	nistry of Labor - Regulation Respectir	C C	wironment)
Components	Туре	Value	Form
			FUIII
Aluminum (7429-90-5)	TWA	10 mg/m3	
		5 mg/m3	Welding fume.
Copper (7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Lead (7439-92-1)	TWA	0.05 mg/m3	
Manganese (7439-96-5)	STEL	3 mg/m3	Fume.
	TWA	1 mg/m3	Fume.
		5 mg/m3	Dust.
Nickel (7440-02-0)	TWA	1 mg/m3	
Tin (7440-31-5)	TWA	2 mg/m3	
Mexico. Occupational Expo	sure Limit Values		
Components	Туре	Value	Form
Aluminum (7429-90-5)	TWA	5 mg/m3	Pyrophoric powder.
		10 mg/m3	Dust.
		5 mg/m3	Welding fume.
Copper (7440-50-8)	STEL	2 mg/m3	Fume.
		2 mg/m3	Dust and mist.
	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Lead (7439-92-1)	TWA	0.15 mg/m3	Dust and fume.
Manganese (7439-96-5)	STEL	3 mg/m3	Fume.
manganooo (1+00-00-0)	TWA	1 mg/m3	Fume.
		0.2 mg/m3	rumo.
Nickel (7440-02-0)	TWA	1 mg/m3	
Tin (7440-31-5)	STEL	4 mg/m3	
( <i>1</i> ++0-31-3)	TWA	•	
		2 mg/m3	
ineering controls	Provide adequate ventilation. Observe inhalation of dust. Ventilate as needed equipment if airborne dust levels are h divided metallic dust generated by grin	d to control airborne dust. Use high. Special ventilation should	explosion-proof ventilatior be used to convey finely
	Follow the schedule for work place me		
sonal protectivo oquipment	• • • •	5	
sonal protective equipment	· · · · · · · · · · · ·		
Eye / face protection	Wear dust-resistant safety goggles wh glasses or goggles, a welding helmet burning, or brazing. A face shield is re	with appropriate shaded shield commended, in addition to saf	is required during welding
	during sawing, grinding, or machining.		

Respiratory protection	When engineering controls are not sufficient to lower exposure levels below the applicable exposure limit, use a NIOSH approved respirator for dusts. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever work place conditions warrant a respirator's use. Seek advice from local supervisor. In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment with particle filter.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately. Contaminated uniforms should be laundered separately from other clothing to prevent potential cross-contamination. If possible, an industrial laundry service should be used to eliminate the possibility of contaminating the home environment. Handle in accordance with good industrial hygiene and safety practices. Observe any medical surveillance requirements.

### 9. Physical & Chemical Properties

Appearance	Shapes, Solids, Tubes & Turnings.
Color	Yellow to red.
Odor	None.
Odor threshold	Not available.
Physical state	Solid.
Form	Solid. Shapes, Solids, Tubes & Turnings.
рН	Unknown.
Melting point	1616 - 1725.8 °F (880 - 941 °C)
Freezing point	Not available.
Boiling point	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Specific gravity	Not available.
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Bulk density	0.27 - 0.323 lb/in ³ (20°C/68°F)

# 10. Chemical Stability & Reactivity Information

Chemical stability	Massive metal is stable and non reactive under normal conditions of use, storage and transport.
Conditions to avoid	Contact with incompatible materials. Contact with acids will release flammable hydrogen gas. Avoid dust formation. Dust clouds may be explosive under certain conditions.
Incompatible materials	Acids. Ammonium nitrate. Fluoride. Halogens. Nitrates. Phosphorus. Strong oxidizing agents. Sulphur.
Hazardous decomposition products	Welding, burning, sawing, brazing, grinding or machining operations may generate dusts and fumes of metal oxides. Lead oxide fumes may be formed at elevated temperatures. Phosphorus oxides. Aluminium oxides.
Possibility of hazardous reactions	Hazardous polymerization does not occur. Hot molten material will react violently with water resulting in spattering and fuming.

## **11. Toxicological Information**

Acute e	effects
---------	---------

Harmful if inhaled or swallowed. Dusts may irritate the respiratory tract, skin and eyes. High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever.

Local effects	May cause irritation through mechanical abrasion.		
Sensitization	May cause allergic skin reaction.		
Chronic effects	Chronic exposure to breathing low levels of manganese dust or fume over a long period of time can result in "manganism," a disease of the central nervous system similar to Parkinson's Disease, gait impairment, muscle spasms and behavioral changes. Repeated overexposure to manganese over time may adversely affect the male reproductive system and central nervous system. Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis (stannosis). Chronic inhalation of metallic oxide dust/fume may cause metal fume fever. Lead may produce maternal toxicity, toxicity to the fetus, and adverse effects to blood, bone marrow, central/peripheral nervous systems, kidney, liver, and reproductive system.		
Carcinogenicity	Possible cancer hazard - may cause cancer based on animal data.		
ACGIH Carcinogens			
Aluminum (CAS 7429-90 Lead (CAS 7439-92-1)	A3 Confirmed animal carcinogen with unknown relevance to humans.		
Nickel (CAS 7440-02-0)	A5 Not suspected as a human carcinogen.		
	Evaluation of Carcinogenicity		
Lead (CAS 7439-92-1)	2B Possibly carcinogenic to humans.		
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans. ens: Anticipated carcinogen		
Lead (CAS 7439-92-1)	Anticipated carcinogen.		
Nickel (CAS 7439-92-1)	Anticipated carcinogen.		
US NTP Report on Carcinog			
Nickel (CAS 7440-02-0)	Known carcinogen.		
Epidemiology	Based on epidemiological studies, pre-existing pulmonary disorders may be aggravated by prolonged exposure to high concentrations of metal dust or fumes. Pre-existing skin conditions including dermatitis might be aggravated by exposure to this product.		
Mutagenicity	No data available.		
Neurological effects	Exposure to manganese fume/dust can affect the central nervous system (apathy, drowsiness, weakness and other chronic symptoms such as postural tremors).		
Reproductive effects	Contains a substance/a group of substances which may cause harm to the unborn child.		
Teratogenicity	Nickel: Has shown teratogenic effects in laboratory animals.		
Further information	Lead is accumulated in the body and may cause damage to the brain and nervous system after prolonged exposure. Welding or plasma arc cutting of metal and alloys can generate ozone, nitric oxides and ultraviolet radiation. Ozone overexposure may result in mucous membrane irritation or pulmonary discomfort. UV radiation can cause skin erythema and welders flash.		
12 Ecological Information			

# 12. Ecological Information

Ecotoxicological data Components	Test Results	
Lead (7439-92-1)	LC50 Rainbow trout, donaldson trout (Oncorhynhus mykiss): 1.17 mg/l 96 Hours	
Ecotoxicity	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
Persistence and degradability	The product is not biodegradable.	
Bioaccumulation / Accumulation	The product contains potentially bioaccumulating substances.	
Partition coefficient (n-octanol/water)	Not available.	
Mobility in environmental media	Alloys in massive forms are not mobile in the environment.	
13. Disposal Considerations		

Waste codes	Not regulated.
Disposal instructions	This material and its container must be disposed of as hazardous waste. Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Recover and recycle, if practical. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.

Contaminated packaging Not applicable. 14. Transport Information DOT Not regulated as dangerous goods. ΙΑΤΑ Not regulated as dangerous goods. IMDG Not regulated as dangerous goods. TDG Not regulated as dangerous goods. 15. Regulatory Information **US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List. TSCA Section 12(b) Export Notification(40 CFR 707, Subpt. D) Not regulated. US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration 1.0 % Aluminum (CAS 7429-90-5) Copper (CAS 7440-50-8) 1.0 % Lead (CAS 7439-92-1) 0.1 % Substance is not eligible for the de minimis exemption except for the purposes of supplier notification requirements. Manganese (CAS 7439-96-5) 1.0 % Nickel (CAS 7440-02-0) 0.1 % US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Reportable threshold Lead (CAS 7439-92-1) 100 LBS US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance Aluminum (CAS 7429-90-5) Listed. Copper (CAS 7440-50-8) Listed. Lead (CAS 7439-92-1) Listed. Manganese (CAS 7439-96-5) Listed. Nickel (CAS 7440-02-0) Listed. CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4) Copper: 5000 Nickel: 100 Lead: 10 Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Section 302 extremely No hazardous substance (40 CRF 355, Appendix A) Section 311/312 (40 CFR Yes 370) Drug Enforcement Not controlled Administration (DEA) (21 CFR 1308.11-15) **Canadian regulations** This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS status Controlled WHMIS classification D2A - Other Toxic Effects-VERY TOXIC D2B - Other Toxic Effects-TOXIC

 $(\underline{I})$ 

#### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Yes Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compon	ents of this product comply with the inventory requirements administered by the gov	erning country(s)
State regulations	WARNING: This product contains a chemical known to the State of California	rnia to cause cancer.
US - California Hazardous Su	ubstances (Director's): Listed substance	
Aluminum (CAS 7429-90- Copper (CAS 7440-50-8) Lead (CAS 7439-92-1) Manganese (CAS 7439-94 Nickel (CAS 7440-02-0) Tin (CAS 7440-31-5) <b>US - California Proposition 6</b> Lead (CAS 7439-92-1)	Listed. Listed.	
Nickel (CAS 7440-02-0)	Listed.	
US - California Proposition 6	5 - CRT: Listed date/Carcinogenic substance	
Lead (CAS 7439-92-1) Nickel (CAS 7440-02-0) US - California Proposition 6	Listed: October 1, 1992 Carcinogenic. Listed: October 1, 1989 Carcinogenic. 5 - CRT: Listed date/Developmental toxin	
Lead (CAS 7439-92-1) US - California Proposition 6	Listed: February 27, 1987 Developmental 5 - CRT: Listed date/Female reproductive toxin	toxin.
Lead (CAS 7439-92-1) US - California Proposition 6	Listed: February 27, 1987 Female reprodutive toxin	uctive toxin.
Lead (CAS 7439-92-1)	Listed: February 27, 1987 Male reproduct	ive toxin.
US - Massachusetts RTK - Si Aluminum (CAS 7429-90- Copper (CAS 7440-50-8) Lead (CAS 7439-92-1) Manganese (CAS 7439-94 Nickel (CAS 7440-02-0) Tin (CAS 7440-31-5)	5) Listed. Listed. Listed.	
	RTK (EHS Survey): Reportable threshold	
Aluminum (CAS 7429-90- Copper (CAS 7440-50-8) Lead (CAS 7439-92-1) Manganese (CAS 7439-94 Nickel (CAS 7440-02-0)	5) 500 LBS 500 LBS 500 LBS 500 LBS 500 LBS 500 LBS 500 LBS	
US - New Jersey RTK - Subs		
Aluminum (CAS 7429-90- Copper (CAS 7440-50-8) Lead (CAS 7439-92-1)	5) Listed. Listed. Listed.	

Manganese (CAS 7439-9	6-5)	Listed.	
Nickel (CAS 7440-02-0)		Listed.	
Tin (CAS 7440-31-5)		Listed.	
-	zardous Substances: All com	pounds of this substance are considered environmental	
hazards			
Copper (CAS 7440-50-8)		LISTED	
Lead (CAS 7439-92-1)		LISTED	
Manganese (CAS 7439-9	6-5)	LISTED	
Nickel (CAS 7440-02-0)		LISTED	
US - Pennsylvania RTK - Ha	zardous Substances: Listed s	ubstance	
Aluminum (CAS 7429-90-5)		Listed.	
Copper (CAS 7440-50-8)		Listed.	
Lead (CAS 7439-92-1)		Listed.	
Manganese (CAS 7439-96-5)		Listed.	
Nickel (CAS 7440-02-0)		Listed.	
Tin (CAS 7440-31-5) Listed.			
US - Pennsylvania RTK - Ha	zardous Substances: Special	hazard	
Nickel (CAS 7440-02-0) Special hazard.		Special hazard.	
16. Other Information			
Recommended use	Manufacturing		
Recommended restrictions	Not assigned.		
Further information	HMIS® is a registered trade and service mark of the NPCA. X - Specialized Handling		
Other information	None known.		
HMIS® ratings	Health: 2*		
	Flammability: 0		
	Physical hazard: 0		
	Personal protection: X		
NFPA ratings	Health: 2		
	Flammability: 0		
	Instability: 0		
Disclaimer	The information in this MSDS was obtained from industry sources that we believe to be reliable. However, the information is provided without any representation or warranty, expressed or implie		
		rectness. The conditions or methods of handling, storage, use, and	
	disposal of the product are beyond our control and may be beyond our knowledge. For this and		
	other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage,		
		any way connected with the handling, storage, use, or disposal of	
	the product.		
Issue date	06-30-2011		